

AUXILIARY RELAY AR 1

AR 1 auxiliary relay converts a 24 Vac or 24 Vdc control signal into a potential-free contact output. The width of the unit is 13 mm.

AR 1 loads the control signal with 20 mA (24 Vac). AR 1 has one normally open contact 230V, 10A (res.). Wires are connected to 2,5 mm² terminals.



Technical data:

| | |
|------------------------|---------------------------------|
| Control signal | 24 Vac, 0.5 VA 24 Vdc, 0.4 W |
| Contact | 230 Vac, 10 A res. |
| Dimensions (w x h x d) | 13 x 85 x 48 mm |

Connection:

| | | |
|----|-----------------------|-----------|
| a | control | 24 Vac/dc |
| b | control | 0 Vac/dc |
| 11 | common contact | (C) |
| 14 | normally open contact | (NO) |

Ordering guide:

| Model | Product number | Description |
|-------|----------------|--|
| AR 1 | 1183010 | auxiliary relay with normally open (NO) contact, relay width 13 mm |

Products fulfil the requirements of directives 73/23/EEC and 2004/108/EY and are in accordance with the standards EN60947, EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).

Produal Oy

Keltakalliontie 18
48770 Kotka
FINLAND
www.produal.fi

Tel: +358-5-230 9200
Fax: +358-5-230 9210
info@produal.fi