

CUT-OFF AND MANUAL CONTROL UNIT FOR ANALOG SIGNAL AUT 6

AUT 6 manual control unit is used with a control system to cut off and to control analog motor signals manually. A total of six (6) analog outputs can be controlled simultaneously.

AUT unit has six auto/manual switches to choose the motor signal either from the control unit or manual control.



Technical data:

Supply 24 Vac/dc, 1VA
Manual control 0...10 V, 10 mA

Dimensions (w x h x d) 90 x 77 x 42 mm

Connection:

X1	analog signal 1 in
X2	analog signal 2 in
X3	analog signal 3 in
X4	analog signal 4 in
X5	analog signal 5 in
X6	analog signal 6 in
G0	supply voltage 0 level
G	supply voltage 24 Vac
Y1	analog signal 1 out
Y2	analog signal 2 out
Y3	analog signal 3 out
Y4	analog signal 4 out
Y5	analog signal 5 out
Y6	analog signal 6 out

Ordering guide:

Model	Product number	Description
AUT 6	1182030	manual control unit

Products fulfill the requirements of directive 2004/108/EY and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).

Produal Oy

Keltakalliontie 18
48770 Kotka
FINLAND
www.produal.fi

Tel: +358-5-230 9200
Fax: +358-5-230 9210
info@produal.fi