

RY 1-KK RELAY WITH AN ON-OFF-AUTO SWITCH

RY 1-KK is a relay, controlled by a 24Vac/dc signal or by an ON-OFF-AUTO switch.

Output is a potential-free change-over contact for max. 230Vac 10A res. load.

RY 1-KK relay can be used with logics outputs working directly or reverse.

There is a LED indicating the state of the relay.

Relay is loading the control signal about 20 mA (24 Vac).



Technical data:

Supply	24V ac/dc
Control signal	24 Vac, 0,5 VA 24 Vdc, 0,4 W
Output contact	pot.free change-over contact 230 Vac, 10 A (res.)
Terminals	2,5 mm ²
Dimensions w x h x d	22,5 x 77 x 52,5 mm

Wiring 1: for direct logics

1	supply	24 Vac/dc
2	control signal	24 Vac/dc
3	supply / control signal	0 V
11	common contact	(C)
12	normally closed contact	(NC)
14	normally open contact	(NO)

Wiring 2: for reverse logics

1	supply	0 V
2	control signal	0 V
3	supply / control signal	24 Vac/dc
11	common contact	(C)
12	normally closed contact	(NC)
14	normally open contact	(NO)

Ordering guide:

Model	Product number	Description
RY 1-KK	1183030	auxiliary relay with a change-over contact and with an ON-OFF-AUTO switch

Products fulfil the requirements of directives 73/23/EEC and 2004/108/EY and are in accordance with the standards EN60947, EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).

Produal Oy

Keltakalliontie 18
48770 Kotka
FINLAND
www.produal.com

Tel: +358-5-230 9200
Fax: +358-5-230 9210
info@produal.fi