

# **TEKV-M FROST GUARD TRANSMITTER / CONTROLLER**

TEKV-M Modbus temperature transmitter is designed for automatic HVAC system to monitoring the air heater radiators against frost. Transmitter information can be used to control other device in the HVAC system.

Temperature is measured by a Pt1000 element. . The sensor element resistance information is converted into a 0...10 V signal and this voltage signal is available also via Modbus. The temperature range can be chosen at the commissioning.

TEKV-M settings can be changed by using the ML-SER tool. One point field calibration of the transmitter can be executed, the temperature output can be changed to the controller function and the communication settings of the Modbus can be configured.

TEKV-M transmitter can be equipped with a 3.5-digit liquid crystal display option TE-N V2. The display resolution is 0.1  $^{\circ}$ C.

Housing is made of heat resistant plastics. The bayonet cover and the terminal blocks tilted to  $45^{\circ}$  make an easy installation. The material of the stem is stainless steel for prolonged life. Installation to the radiator is made by means of an R1/4" joint. Mounting depth is adjustable to max. 210 mm. Time constant of the sensor is ca 2.5 seconds.

## **Range selection**

0+50 °C	*0+100 °C	-50+50 °C	-50+150 °C
S1 S2	S1 S2	S1 S2	S1 S2
• •		••	$\bullet \bullet \bullet \bullet$

\* = factory setting

## **Output signal**

0+50	0+100	-50+50	-50+150	Signal
0 °C	0 °C	-50 °C	-50 °C	0 V
25 °C	50 °C	0 °C	50 °C	5 V
50 °C	100 °C	50 °C	150 °C	10 V



### **Technical data:**

supply voltage	24 Va
sensor	Pt100
output 1 output 2 temperature range	010 RS-48 select
connection	R ¼"
stem	Ø 4 m
housing	plastic
protection class	IP54,
cable entry	M16
pressure rating	PN16
accuracy	± 0.5
ambient temperature	0+6
time constant	ca 2.5

24 Vac/dc < 1 VA (22...30Vac/dc) Pt1000 EN 60751/B 0...10 Vdc < 2 mA (temp. / controller) RS-485 Modbus/RTU selectable R  $\frac{1}{4}$ " Ø 4 mm x 234 mm, material AISI316 plastics (< 120 °C) IP54, cable entry or stem down M16 PN16  $\pm$  0.5 °C (at 50 °C) 0...+60 °C ca 2.5 s

## Wiring:

- 1 supply 24 Vac/dc
- 2 0 V
- 3 output 0...10 Vdc (temperature / controller)
- 4 Modbus A+
- 5 Modbus B-

#### Ordering guide:

Model	Product num- ber	Description
TEKV-M	117Z120	Modbus frost guard transmitter
TE-N V2	1170250	display module (cover)
ML-SER	1139010	transmitter commissioning tool

Products fulfill the requirements of directive 2004/108/EC and are in accordance with the standards EN61000-6-3: 2001 (Emission) and EN61000-6-2: 2001 (Immunity).

Produal Ov

 Keltakalliontie 18, 48770 Kotka FINLAND
 Tel: +358-10-219 9100 / Fax: +358-5-230 9210

 Information is subject to change without prior notice.